



#	PART NAME	PART NUMBER	QTY	SPEC	TOOL	TORQUE		COMMENT
						Nm	in-lbf	
A	Chain Ring	S211400009	1	SRAM EAGLE 34 Teeth 104 mm BCD STEEL EMTB W/BOLTS	N/A	N/A	N/A	
B	Chain Ring Bolts		4		5 mm hex	10	89	
C	Spider	S195100001	1	SPIDER,104 mm BCD	N/A	N/A	N/A	
D	Spider Groove Nut	S166800011	1	Levo ISIS Groove Nut	ParkTool BBT-18 or Shimano TL-UN96	50	443	
E	Crank	VARIOUS		Carbon & Alloy 160 mm	8 mm hex	40	354	Compatible with Levo Gen2; 165 mm Cranks
F	Brose Cap Puller	S175300006	1		N/A	N/A	N/A	
G	O-Ring	S221600011	1	O-RING, 23.5 mm ID x 2.4 mm OD, Drive Side	Grease	N/A	N/A	

- 1: Remove the spider groove nut from the spindle.
- 2: Place the Brose cap puller over motor spindle
- 3: Locate the jaws of the 2-jaw puller under the spider with the screw tip located on the cap.
- 4: By turning the handle on the 2-jaw puller, slowly remove the spider from the spindle.

CRANK CARBON NDS 160 mm	<a href="#">S211600021</a>	CRANK CARBON NDS 165 mm	<a href="#">S211600008</a>
CRANK CARBON DS 160 mm	<a href="#">S211600020</a>	CRANK CARBON DS 165 mm	<a href="#">S211600007</a>
CRANK ALLOY NDS 160 mm	<a href="#">S211600019</a>	CRANK ALLOY NDS 165 mm	<a href="#">S201600022</a>
CRANK ALLOY DS 160 mm	<a href="#">S211600018</a>	CRANK ALLOY DS 165 mm	<a href="#">S201600021</a>