

MODEL		TURBO LEVO	COMP	CARBON COMP	EXPERT	S-WORKS
DRIVETRAIN						
CHAIN		KMC X11ET, 11-speed w/ Missing Link™	KMC X11ET, 11-speed w/ Missing Link™	KMC X11ET, 11-speed w/ Missing Link™	KMC X11ET, 11-speed w/ Missing Link™	SRAM XX1, 11-speed
CRANKSET		Praxis, 2D cold-forged alloy, custom offset, 165mm	Praxis, 2D cold-forged alloy, custom offset, 165mm	Praxis, 2D cold-forged alloy, custom offset, 165mm	Praxis, 2D cold-forged alloy, custom offset, 165mm	Praxis, full carbon ISIS, custom offset, 165mm
SHIFT LEVERS		SRAM S700, single-click lever	SRAM S700, single-click lever	SRAM S700, single-click lever	SRAM S700, single-click lever	SRAM X01, single-click lever
CASSETTE		SRAM PG-1130, 11-speed, 11-42t	SRAM PG-1130, 11-speed, 11-42t	SRAM PG-1130, 11-speed, 11-42t	SRAM XG-1175, 11-speed, 10-42t	SRAM XG1199, XD, 11-speed, 10-42t
CHAINRINGS		32T, custom steel	32T, custom steel	32T, custom steel	32T, custom steel	32T, custom steel
REAR DERAILLEUR		SRAM NX, 11-speed	SRAM GX, long cage, 11-speed	SRAM GX, long cage, 11-speed	SRAM X1, 11-speed	SRAM XX1, 11-speed
SUSPENSION						
REAR SHOCK		RockShox Deluxe RT w/ custom air valve, 150mm of travel	RockShox Deluxe RT w/ custom air valve, 150mm of travel	FOX DPS Performance, 210x52.5, 150mm of travel, 3-Position Adjustment, custom tune	RockShox Deluxe RT3 w/ custom valve, 150mm of travel	FOX FLOAT Factory DPS, 210x52.5, 150mm of travel
WHEELS						
FRONT HUB		Specialized, sealed cartridge bearings, 15x110mm thru-axle, 28h	Specialized, sealed cartridge bearings, 15x110mm thru-axle, 28h	Specialized, sealed cartridge bearings, 15x110mm thru-axle, 28h	Specialized, sealed cartridge bearings, 15x110mm thru-axle, 28h	Roval Traverse SL, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 28h
REAR HUB		Specialized, sealed cartridge bearings, 12x148mm thru-axle, 28h	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 28h	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 28h	DT Swiss 360, 3-pawl design, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
INNER TUBES		Standard, Presta valve	Standard, Presta valve	Standard, Presta valve	Standard, Presta valve	Standard, Presta valve
SPOKES		DT Swiss Industry	DT Swiss Industry	DT Swiss Industry	DT Swiss Revolution	DT Competition Race
RIMS		Roval Traverse 29, hookless alloy, 30mm inner width, tubeless ready	Roval Traverse 29, hookless alloy, 30mm inner width, tubeless ready	Roval Traverse 29, hookless alloy, 30mm inner width, tubeless ready	Roval Traverse 29, hookless alloy, 30mm inner width, tubeless ready	Roval Traverse SL, hookless carbon, tubeless ready
FRONT TIRE		Butcher, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"	Butcher, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"	Butcher, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"	Butcher, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"	Butcher, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"
REAR TIRE		Butcher, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"	Butcher, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"	Butcher, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"	Butcher, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"	Butcher, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"
COCKPIT						
SADDLE		Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm	Body Geometry Phenom Expert, hollow titanium rails, carbon fiber base, 143mm

SEATPOST		Specialized 2-bolt head, forged alloy, 5mm offset, micro-adjust, 34.9mm	X-Fusion Manic, 34.9mm, 125mm of travel (Small), 150mm of travel (M/XL)	X-Fusion Manic, 34.9mm, 125mm of travel (Small), 150mm of travel (M/XL)	Specialized Command Post 34.9mm, 130mm of travel (Size: Small), 160mm of travel (Sizes: M/XL)	Specialized Command Post 34.9mm, 130mm of travel (Size: Small), 160mm of travel (Sizes: M/XL)
STEM		Specialized Trail, 3D-forged alloy, 4-bolt, 6-degree rise	Specialized Trail, 3D-forged alloy, 4-bolt, 6-degree rise	Specialized Trail, 3D-forged alloy, 4-bolt, 6-degree rise	Specialized Trail, forged alloy, 4-bolt, 6-degree, S/M 40mm / L/XL 50mm	Deity Copperhead, 31.8mm
HANDLEBARS		Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 780mm, 31.8mm clamp	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 780mm, 31.8mm clamp	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 780mm, 31.8mm clamp	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 780mm, 31.8mm clamp	Specialized Trail, FACT Carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm, 31.8mm
GRIPS		Specialized Sip Grip	Specialized Sip Grip	Specialized Sip Grip	Specialized Sip Grip	Specialized Sip Grip
BRAKES						
FRONT		SRAM Level T, hydraulic disc, 4-Piston Caliper, 200mm	SRAM Guide RE, 4-piston caliper, hydraulic disc, 200mm	SRAM Guide RE, 4-piston caliper, hydraulic disc, 200mm	SRAM Code R, 4-piston caliper, hydraulic disc, 200mm	SRAM Code RSC, 4-piston caliper, hydraulic disc, 200mm
REAR		SRAM Level T hydraulic disc, 2-Piston Caliper, 200mm	SRAM Guide RE, 4-piston caliper, hydraulic disc, 200mm	SRAM Guide RE, 4-piston caliper, hydraulic disc, 200mm	SRAM Code R, 4-piston caliper, hydraulic disc, 200mm	SRAM Code RSC, 4-piston caliper, hydraulic disc, 200mm
FRAMESET						
SEATBINDER		Alloy, 38.6mm	Alloy, 38.6mm	Alloy, 38.6mm	Alloy, 38.6mm	Specialized Ti-bolt-type, alloy, 38.6mm
FORK		RockShox Sektor RL, 29" Boost™, 150mm of travel	RockShox Revelation Charger RC, 29" Boost™, 150mm of travel	FOX 34 Rhythm E-bike, GRIP damper, 29" Boost™, 150mm of travel	RockShox Pike RC29, 150mm of travel	FOX 36 Factory E-bike, GRIP2 damper, 29" Boost™, 150mm of travel
FRAME		Specialized M5 Premium Aluminum, 29 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel	Specialized M5 Premium Aluminum, 29 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel	FACT 9m Carbon w/ M5 alloy rear triangle, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel	FACT 9m Carbon w/ M5 alloy rear triangle, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel	S-Works FACT 11m full carbon, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
WEIGHT		22KG	22.1KG	21.3KG	21.3KG	20.7KG
Battery						
		500wh	500wh	500wh	700wh	700wh